

A25 model



Description

Audolici A25 tube audio amplifier, is an excellent demonstration of consonance between audio reproduction epochs. Uses advanced technology based on the best tradition of tube construction practice's from the 70's. It reproduces the signal of different sources, with high quality and resolution. The music displayed by the **A25** model, reveals dynamics and natural tone, both at the instrument and at the vocal level. Each output section is equipped with bias adjustment trimmer for individual approximation.

This power amplifier that outputs 25W per channel, using well sounded Russian original standard valves "Tungsol" **6SL7(2)** and **EL-34B(4)**, selected with individual strict criteria. Each tube has special fluid and crisp sound character, which especially determines a different music style. All models are hand numbered.

Specifications

Two channels

Four inputs(CD/Tunner/Aux1/Aux2)

Phono output

A25: 2x25w

Loudspeaker impedance: 4-6 Ω or 6-8 Ω

Frequency response: 28Hz-20KHz/ \pm 1,5dB@20W

Line

Input sensitivity: 1,57 V

Signal to noise ratio: 89dB

Dumping factor: 10@1KHz

Channel separation: 20dB@1KHz -50dB

Tubes: EL-34B "Tungsol" (4), 6SL7 (2)

Power consumption: 280VA

Dimensions: 435 x 90 x 330mm

Weight: 11,5 kg

Mains: 230V/115V

Input terminals: gold plated RCA

More info

www.audolici.com